



Commercial Substrate Evaluation Report

Certified for **HP Indigo**

Supplier Information								
Supplier Name Neenah Paper								
Supplier Address	135 N. Commercial S	135 N. Commercial St., Neenah, WI, 54956						
Supplier Country	USA	USA						
Product Information								
Product Name	Neenah® Color Copy	Neenah® Color Copy 100C Super Smooth Solar White						
Product Category	Paper	Paper						
Grammage (gsm) / Basis weight	#) 100#	100#		Thickness (microns/caliper)		11.5 mils/0.0115 in/11.5 Pts		
Certification Number	RI5500-15-4240	RI5500-15-4240		Certification Center		RIT		
Date of Evaluation	11/24/2015	11/24/2015			HP 5500			
Certified for	5500, 5600 multi-shot	5500, 5600 multi-shot, 7000, 7500, 7600, 7800 & 10000						
Evaluation Process	Full							
Evaluation	Measurement		Result	Gı	ade (stars)	Comments		
Runability								
Simplex	Number of Jams	0		***				
Duplex	Number of Jams	0						
Ink Adhesion / Fixing				**	*			
Ink Adhesion / Fixing Peeling	100%K in 4 color mode, % in remaining	100%		**	*			
				**	*			
Peeling	% in remaining	100%		**	*			
Peeling Flaking	% in remaining <1 mm, % Coverage 290K in 4 color mode,	100%		**	*			

N/A

Pass

>80% after 10 or 60 min

1st clean page after 12K impressions

Comment Detail:

White Ink Recommended

Blanket Compatibility

Cleaner Pages

Evaluation Result

The substrate certification procedure incorporates several processes.

An initial screening evaluation is followed by a more comprehensive evaluation looking at the performance of the particular substrate within the press. This checks for:

Runnability:

The ability of the substrate to run smoothly through the press in various print modes.

Fixing:

Ink-substrate interaction as determined by: 1) The degree of ink adhesion to the substrate for standard and photo-related applications as measured in a tape peel test of the image; and 2) The degree of flaking of the ink layer. The fixing properties are measured through a range of blanket temperatures and pressures.

Blanket Compatibility:

Blanket-substrate interaction as determined by: 1) Ink-transferability, which is the quality of ink transfer from the blanket to the substrate as reflected in highlight dots, thin lines, heavy images and image edge integrity; 2) 'Blanket Memory' effects, reflected in gloss or density differences between solids and background areas of the previously printed image; and 3) Number of cleaner pages, in which blankets are routinely maintained by performing a self cleaning procedure ("cleaner pages") used to refresh the blanket's release layer.

Photo and White Ink Applications:

Use of robust media products is strongly recommended when printing photo-related and/or white ink applications and/or Light Cyan and Light Magenta due to additional ink coverage demands of these applications. This media has been tested and approved to perform well with higher levels of ink coverage, and is therefore recommended for photo-related and/or white ink type applications. However, it is strongly recommended that user acceptance ultimately be evaluated per individual application and finishing requirements, etc. The test results are provided as a guide; assess actual performance to determine suitability for individual use.

Star Rating



		***	**	*	
Evaluation	Measurement	Best-performing	Recommended	Good	Failure
Transport	Runnability	No jams with the tested paper			2 jams with the tested paper, control performs well
Fixing	Peeling	All 4 results are ≥ 90%	All 4 results are ≥ 80%	At least 1 result is ≥ 80%	All results < 80%
Flaking Guille	Flaking Guillotine, 5min ● Coated		At least 1 result is > 250%	At least 1 result is > 200%	Results < 200%
Flaking Guillotine, 5min ● Uncoated		Result is > 300%	Result is > 250%	Result is > 200%	Results < 200%
Photo	Peeling 290% Black	Result is > 80% o	fter 10 or 60 minutes	N/A	Results < 80%
	Flaking Guillotine, 5min	<1 mm at 350% K		N/A	Results > 1 mm
Blanket Compatibility	Cleaner Sheets	1ª Red is clean	3™ Red is clean	5 th Red is clean	5th Red not clean, or White observed
	Monitors on tested paper and reference glossy paper	Very minor memories at least up to 12K impressions	Slight memories may be seen up to 12K impressions	Some memories may be seen by 12K impressions	Severe lack of dots/cracks/gloss memory

This substrate is certified for the next two years from the date of evaluation, provided there is no change to the paper properties or production processes. At the end of two years from the original evaluation date, if there have been no changes in paper properties or production processes, the certification can be extended for another two years. After four years from the original certification date, a new certification is required.



